135R-103801 REV.: 2 3 1/4 SEISMIC VERTICAL LIMIT STOP, 3/8 OPERATING NUT AND WASHER, TIGHTEN GAP TOGETHER (SEE NOTE 1 & 3) **ELASTOMERIC ELEMENT**  $(1\ 11/16)$ - 5/8 MAX ROD, NUT AND WASHER (SEE NOTE 1) 3/8 MIN AT FREE POSITION (3)**SPRING FREE HEIGHT** SEISMIC VERTICAL LIMIT STOP, 3/8 OPERATING NUT AND WASHER, TIGHTEN **GAP TOGETHER (SEE NOTE 3)** 

TYPE HRS-1C PRE-COMPRESSED ELASTOMERIC & SPRING HANGERS						
FOR 1" NOMINAL DEFLECTION						
HANGER	RATED LOAD	DEFLECTION	SPRING RATE	SPRING	<b>ELEMENT LOAD &amp;</b>	
	(LBS)	(IN)	(LBS/IN)	COLOR CODE	COLOR CODE	
HRS-1C-50PR	50	1.15	50	BLUE	RE-B-170 BLACK	
HRS-1C-100PR	100	1.29	100	TAN	RE-B-170 BLACK	
HRS-1C-150PR	150	1.44	150	RED	RE-B-170 BLACK	

300

400


493

1.16

1.14

1.24

REV.



BLACK

YELLOW

DK YELLOW

DESCRIPTION

DATE

RE-B-380 GREEN

RE-B-380 GREEN

RE-B-380 GREEN

BY

ISOLATOR SELECTIONS		
LOC 1:	LOC 2:	
LOC 3:	LOC 4:	
LOC 5:	LOC 6:	
LOC 7:	LOC 8:	
CUSTOMER EQP'T. TAG:		

NOTE: MATERIAL SHOWN IS FOR (1) SET.

1. HANGER RODS	S, NUTS AND WASHERS, AS SH
WITH REQUIRE	ED INSIDE DIAMETER TO ACOM

NOTES:

- HOWN. NOT BY THE VMC GROUP. INSTALL WASHER .134 THK. MIN. X 1-3/4 O.D. MIN. MMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE THAN TWO WASHERS
- 2. STANDARD FINISH: HANGER BOX PAINTED, POWDER COATED OR GALVANIZED STEEL, SPRING - POWDER COAT.
- 3. SEISMIC VERTICAL LIMIT-STOP HARDWARE REQUIRED FOR SEISMIC APPLICATIONS.
- 4. ALL DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.
- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER. CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.
- 8. HANGER BOXES WITH AN ELASTOMERIC ELEMENT HAVE UP TO AN ADDITIONAL 1/2" NOMINAL DEFLECTION.
- 9. DOUBLE LOWER NUT PROVIDED.

CUSTOMER P.O.:

SALES ORDER:

- 10.ROD EXTENSION BELOW LOWER NUT EXTENDS (1.5XROD DIA.) AS SHIPPED.
- 11.PRE-COMPRESSED 50% OF SPRING RATED DEFLECTION.
- 12.RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS

CERTIFIED FOR:	
JOB NAME:	-
CUSTOMER ·	

MODEL HRS-1C 50-370 LBS. PRE-COMPRESSED **ELASTOMERIC AND SPRING HANGERS** 1 INCH DEFLECTION

HRS-1C-250PR

HRS-1C-300PR

HRS-1C-370PR

250

300

370

THE VMC GROUP

NONE SHEET:

1 OF 1

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR

PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

The Power of Together Bloomingdale, NJ 07403

Houston, TX 77041

DRAWING NO.:

REVISION