
DATE 135R-101274 REV.:5 | 10/20/23 REV. DESCRIPTION



1. HANGER RODS AND NUTS, AS SHOWN, NOT BY THE VMC GROUP.

3. ALL DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.

SALES ORDER:


2. STANDARD FINISH SPRING - POWDER COAT, HARDWARE: ZINC-ELECTROPLATE.

4. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.

TYPE HSO-1D SPRING HANGERS FOR 1" NOMINAL DEFLECTION				
HANGER	RATED LOAD (LBS)	DEFLECTION (IN)	SPRING RATE (LB/IN)	SPRING COLOR CODE
HSO-1D-85	85	1.35	63	LT PURPLE
HSO-1D-120	120	1.20	100	DK YELLOW
HSO-1D-175	175	1.17	150	DK BLUE
HSO-1D-250	250	1.40	179	YELLOW
HSO-1D-340	340	1.13	300	RED
HSO-1D-510	510	1.02	500	BLACK
HSO-1D-675	675	1.32	513	DK PURPLE
HSO-1D-900	900	1.02	881	DK GREEN
HSO-1D-1200	1200	0.90	1327	GRAY
HSO-1D-1360	1360	0.77	1758	WHITE
HSO-1D-1785N1	1785	0.88	2029	GRAY/RED

NOTES:

1. TWO NESTED SPRINGS YIELD THIS LOAD. THE COLOR CODE IS FOR OUTER SPRING/ INNER SPRING.



ISOLATOR SELECTIONS			
LOC 1:	LOC 2:		
LOC 3:	LOC 4:		
LOC 5:	LOC 6:		
LOC 7:	LOC 8:		
CUSTOMER EQP'T. TAG:			

NOTE: MATERIAL SHOWN IS FOR (1) SET.

5. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.

RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS. THE MAXIMUM ROD SIZE FOR HSO-1D-1785N IS 5/8 INCHES

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.



NOTES:

CERTIFIED FOR: JOB NAME: CUSTOMER: CUSTOMER P.O.:

MODEL HSO-1D 85-1785 LBS. **SPRING HANGERS** 1 INCH DEFLECTION



SHEET: 1 OF 1

NONE

Bloomingdale, NJ 07403