


| REV. | DESCRIPTION | DATE | BY |
|------|-------------|------|----|
|      |             |      |    |

| PART NUMBER | MODEL    | RATED AXIAL<br>LOAD (LBS) | DEFLECTION<br>(IN) |
|-------------|----------|---------------------------|--------------------|
| 330620      | R2-BLUE  | 135                       | 0.25               |
| 330523      | R2-BLACK | 170                       | 0.25               |
| 330426      | R2-RED   | 240                       | 0.25               |
| 330329      | R2-GREEN | 380                       | 0.25               |
| 330221      | R2-GRAY  | 790                       | 0.25               |



NOTES:

- 1. ALL DIMENSIONS ARE NOMINAL IN INCHES. INTERPRET PER ANSI Y14.
- MOLDED STEEL AND ELASTOMERIC ISOLATOR FOR NON FAIL SAFE, SERVICE CONDITIONS. CONTACT THE VMC GROUP FOR APPLICABILITY
- 3. MODEL COLORS ARE ACTUAL MOUNT COLOR IN ADDITION TO MODEL TYPE STAMPING.
- 4. ADDITIONAL ELASTOMER TYPES & CAPACITIES AVAILABLE, CONTACT THE VMC GROUP FOR APPLICABILTY.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.



CERTIFIED FOR:

JOB NAME:

CUSTOMER:

CUSTOMER P.O.: \_
SALES ORDER: \_\_

MODEL R2 135-790 LBS. ELASTOMERIC ISOLATOR 0.25 INCH DEFLECTION



THE POWER OF TOGETHER\*
Bloomingdale, NJ 07403
Houston, TX 77041

| NONE   | Memb⊕,                 |
|--------|------------------------|
| SHEET: | ···· <del>·VISCM</del> |
| 1 OF 1 | _                      |
|        |                        |

DRAWING NO.: REVISION

1 1/4

7/32