114R-105066 REV.:2 04/27/20			REV.		DESCRIPT	ION	DATE	BY	
	GRIP RIBS	PART		ELASTOMER RATED AXIAL LOAD-	SHORE A		G COLOR CO	ODE	
CONCENTRI		NUMBER		LBS	DURO ±5	DEFLECTION			
RAISED RING		770054-1 770054-2	RDX1-01 RDX1-02	35 45	32 40	0.4	BLUE		
	GS VIEW "A-A"	770054-2	RDX1-02 RDX1-03	70	50	0.4	RED	·	
└── 5/16-18NC-2B		770054-4	RDX1-04	120	60	0.4	GREEN	1	
		770054-5	RDX1-05	170	70	0.4	YELLO		
	A	770054-8	RDX1-08	35	32	0.4	YELLOW/G	REEN	
A $A$ $A$ $A$ $A$ $A$ $A$ $A$ $A$ $A$				1	<ul><li>3</li><li>4</li></ul>	6	(7) (8)		
NOTES:				ISOLATOR SELECTIONS					
LOC			LOC 1:	LOC 2:					
			LOC 3: LOC 5:	LOC 4: LOC 6:					
3. MOLDED STEEL AND ELASTOMER MOUNT FOR NON-FAIL SAFE,			LOC 7:	LOC 8:					
				R EQP'T. TAG:					
MODEL TYPE.			NOTE: MA	ATERIAL SHOW	/N IS FOR (1	) SET.			
AISOLATOR IS COMPRISED OF 304 STAINLESS STEEL ME	TAL INSERTS.				OTHER MATERIAL PROPERTIES MAY	S, COMPOUNDS, OR FINIS BE SUBSTITUTED AS THE	HES WITH EQUAL O	R SUPERIOR	
CERTIFIED FOR:						SCALE :			
					NONE	Mem	ber		
CUSTOMER :	MODEL RDX1 35-170 LBS. BRIDGE BEARING ELASTOMERIC				٩C	SHEET:	~~~~5	<del>CMR</del>	
CUSTOMER P.O.:	<b>ISOLATOR 0.4 INCH DEFLECTION</b>				GROUP DRAWING NO.: THE POWER OF TOGETHER"			REVISION	
SALES ORDER:				Bloomingda	<b>DF TOGETHER*</b> ale, NJ 07403 , TX 77041				

PROPRIETARY: EXCEPT AS OTHERWISE AGREED IN WRITING, THE INFORMATION AND DESIGN DISCLOSED HEREIN ARE THE PROPERTY OF THE VMC GROUP AND MUST NOT BE COPIED OR DISTRIBUTED OUTSIDE THE VMC GROUP EXCEPT TO AUTHORIZED PERSONS WITH A GENUINE NEED TO KNOW WHO BY THE USE HEREOF ACKNOWLEDGE THE VMC GROUP'S OWNERSHIP AND AGREE TO MAINTAIN THIS INFORMATION AND DESIGN IN STRICT CONFIDENCE.